



WTRTEC

Multi-Parameter

Controller







WTRTEC BLUE

Multi-parameter controller for adjusting free chlorine and pH in drinking water reservoirs, with ORP (Red-Ox) safety measurement.

- Monitoring the water filling flow
- Correction of chlorine dosing
- Proportional to the water inlet



Multi-parameter controller for adjusting free chlorine and pH online with ORP (Red-Ox) safety measurement.

- Chlorine sensor directly installed in the pipe
- Monitoring the water flow
- Online PIQ control with dosing correction according to the water flow



Multi-parameter controller for adjusting free chlorine, pH and electrical conductivity in cooling towers.

- Free-chlorine reading in a wide range of pH (from 6.5 to 9.0)
- Automatic correction of chlorine dosing with the water inlet
- Volumetric dosing of biocide for shock treatments

WTRTECRED

Controller for adjusting pH in the tank or in-line.

- Dual control output for neutralising with acid and base
- Online PIQ control with dosing correction according to the water flow to be treated

WTRTEC GREEN

Multi-parameter controller for proportional dosing of fertilizers and pH adjusting in-line.

- Dosing fertilisers with PIQ proportional adjustment of the electrical conductivity
- Monitoring the flow and proportional dosing
- Online pH control with adjustment to the PIQ flow







TECHNICAL FEATURES

INPUTS	MODELS						
	BLUE	WHITE	GREY	RED	GREEN		
Cl ₂	Х	Х	х				
ORP (RedOx)	Х	Х					
рН	Х	Х	Х	Х	х		
Flow	X	Х	Х	Х	Х		
EC			Х		×		
Flow Detector	Х	Х	Х	Х	×		
STROKES/MIN.	Х	X	Х	Х	×		

OUTPUTS	MODELS						
	BLUE	WHITE	GREY	RED	GREEN		
Pump Output Cl	Х	Х	Х				
Pump Output pH	X	Х	Х	Х	Х		
Pump Output Proportional					х		
Control PIQ CI		Х					
Control PIQ pH		Х		х	Х		
Control PIQ EC				Х	Х		
ALM CI	Х	Х	Х				
ALM ORP	Х	Х					
ALM pH	Х	Х	Х	Х	Х		
ALM Flow		Х		Х	Х		
ALM EC			Х		Х		

Electrical Supply

100-250 V AC /10.8 - 14.4 V DC

Protection

IP65

Temperature

0 - 45 °C

Control/Register mA output

2 Configurables


Control Output Relay

2 Configurables


Alarm Output Relay

3 Configurables

DIMENSIONS









Multi-Parameter Controller

- Online PIQ Control
- CL, PH, ORP, EC, °C/°F, M3/H / GPH
- **⊘** Web/App Remote Control (IoT)





Management System ISO 9001:2008

www.tuv.com ID 9105017955





Helix Hydro Pty. Ltd. 23 Sir Laurence Drive Seaford, Victoria 3198 Phone: 03 9580 2122

Contact: enquiries@helixhydro.com.au Website: www.helixhydro.com.au VIC/TAS P: 0427 033 967 WA/NT P: 0409 115 895 NSW/ACT P: 0414 675 663 QLD P: 0417 733 508 SA P: 0427 033 967

